



A



B



图纸编码

Phase	2	Temperature Rise	Below 80K
Step Angle	1.8°	Insulation Withstand Voltage	500V A.C
Step Angle Error (No Load)	±0.09° or below	Insulation Resistance	Above 100 MΩ
Rated Voltage	2.4 V	Insulation Class	B
Rated Current	5.0 A	Operating Temperature Range	-20°C~+50°C
Resistance (Phase)	0.47 Ω±10%	Operating Humidity Range	20%RH~90%RH
Inductance (Phase)	1.7 mH±20%	Storage Temperature Range	-20°C~+70°C
Holding Torque	3.0 N.m	Storage Humidity Range	15%RH~95%RH
Weight	≈1.35kg		
Rated Operating Status	Continuous		
Lifetime (Hours)	Above 5000H		

版本 Rev

A1.0

变更内容
Revision Record


初次发放

签字 The signature


日期 Date

2023.06.07


Wire Color and Connection Diagram of the Motor



Excitation Sequence (2-Phase Excitation)



Label Content



Note: The lead colors and wiring order are subject to the actual object.

客户签字确认

标记

处数

更改文件号

签名 年月日

视图方式:



比例



SMB2404

TWO-PHASE HYBRID STEPPER MOTOR



汉德保电机

WWW.HDBMOTORS.COM